

IMAS GROUP
REAL QUALITY MADE IN ITALY




PRACTICO

PRICELIST




FST20-11	EUR Price
FST20-11-1200	513
FST20-11-1600	605
FST20-11-2000	698
FST20-11-2400	827
FST20-11-2800	890

Price includes three-step speed regulator Z-VD001.




FST40-11	EUR Price
FST40-11-1200	574
FST40-11-1600	679
FST40-11-2000	784
FST40-11-2400	888
FST40-11-2800	992


Price includes three-step speed regulator Z-VD001.




FSK20-11	EUR Price
FSK20-11-1200	244
FSK20-11-1600	290
FSK20-11-2000	335
FSK20-11-2400	380
FSK20-11-2800	438



FSK40-11	EUR Price
FSK40-11-1200	294
FSK40-11-1600	356
FSK40-11-2000	418
FSK40-11-2400	480
FSK40-11-2800	542



FSK41-11	EUR Price
FSK41-11-1200	275
FSK41-11-1600	333
FSK41-11-2000	390
FSK41-11-2400	448
FSK41-11-2800	506



HEATING OUTPUT TABLE, TEMPERATURE GRADIENT 75/65/20°C, MEDIUM FAN SPEED (TYPE FST)

PRACTIC	Speed	Length [mm] / Output Qn 75/65/20°C [W]					Convector Dimensions (without ledge)
		1200	1600	2000	2400	2800	
<i>with fan</i>							
FST20-11	2	828	1241	1655	1986	2483	261x115mm
FST40-11	2	1394	2090	2787	3344	4181	311x115mm
<i>with natural convection</i>							
FSK20-11	-	114	166	218	270	322	141x115mm
FSK40-11	-	284	414	543	672	802	311x115mm
FSK41-11	-	223	325	426	527	629	261x115mm

THERMOSTATS

Z-DS002 | Simple fan speed switch

Switch levels: 0, 1, 2, 3
 Operating voltage: 230V/50Hz
 Max. switched current: 6 (2) A
 Degree of protection: IP30
 Colour: white
 Dimension: 96 × 97 × 36 mm

€ 18



Z-RT001 | Room thermostat

Temperature range: 10 až 30°C
 Operating voltage: 230V/50Hz
 Max. switched current: 10 (3) A
 Degree of protection: IP30
 Colour: white
 Dimension: 83 × 83 × 40 mm

€ 23



Z-RT005 | Manual room thermostat with speed switch

Temperature range: 8 to 30°C
 Switch levels: 0, 1, 2, 3
 Operating voltage: 230V/50Hz
 Max. switched current: 6 (2) A
 Degree of protection: IP30
 Colour: white
 Dimension: 96 × 110 × 36 mm

€ 37



Z-RT006 | Room temperature controller with LCD and 7-day time program

Temperature range: 5 to 40°C
 Operating modes: Normal operation, Auto Timer (energy saving) and Standby
 Switch levels: 0, 1, 2, 3 or automatic switching
 Operating voltage: 230V/50Hz
 Max. switched current: 4 (2) A
 Degree of protection: IP30
 Colour: RAL 9003 white
 Dimension: 86 × 86 × 46 mm

€ 102



FLOW REGULATION

Z-TS230 | Z-TS230 5m | Thermoelectric actuator 3m | Thermoelectric actuator for thermostat valve control 5m

Operating temperature: 230V AC
 Power input when switch on: 58VA
 Power input during operating: 2,5W
 Period of switching ON/OFF: 210 s
 Ingress protection: IP54 (housing)
 Body-head connection: M30×1,5 mm
 Cable length: Z-TS230 3 meters / Z-TS230 5 meters
 Max. height when opened: 74 mm

€ 29

€ 32



Z-TF001 (available for FSK only) | Radiator thermostat with remote setting

Temperature range: 9 to 26°C, antifreeze temperature 9°C
 Mode: proportional control
 Operating temperature: without additional energy, liquid-filled sensing
 capillara tube length: 5 m
 Body-head connection: M30 × 1,5 mm
 Dimension: 75 × 75 mm, sensor Ø 50 × 68 mm

€ 58



THERMOSTATIC VALVES

Z-TD001 / Z-TE001 | Thermostat. valve direct / corner

DN15, NF norm, M30 × 1,5 mm, PN10, 120°C

Valve adjusting	1	2	3	4	5	N
k_v (m ³ /h)	0,1	0,2	0,31	0,45	0,69	0,89

€ 9

€ 9



Prices are listed in EUR without VAT and delivery. Prices including grill and upper frame.
 The mandatory accessory of FST units is three - step speed regulator Z-VD001. It is included in price.
 Discounts are not provided for accessories and mechanical parts.



IMAS GROUP
REAL QUALITY MADE IN ITALY

NUOVA IMAS Srl

31020 San Zenone degli Ezzelini (TREVISO) ITALY - Street Roma, 163 - Tel. +39 0423 968402 - Fax +39 0423 567216
info@imasradiators.com - www.imasradiators.com